

Charging Cables ICSL5 + ICSL10



Robust & Flexible Cable

Comfortable Handles

Non-Flammable

Carry Case Included

Microfibre Cleaning Mitts Included

Universal - For Single & Three Phase



22KW



Type 2



7KW



Type 2



Connect with iCS
The only link you'll need
for tech support, socials and lots more!
[@icsintelligentchargingsystems](https://www.instagram.com/icsintelligentchargingsystems)



Charging Cables

ICSL5 + ICSL10

Model	Specification	
	ICSL5	ICSL10
Rated Voltage	480v AC	
Rated Current	32A	
Cable Resistance	>5MΩ, 500v DC 1 Min	
Resistance Between PP & PE	220Ω/k	
Conductor Size	L1, L2, L3,N, PE 6mm ² , CP 0.75mm ²	
Cable Length	5m	10m
Working Temperature	-30C to 50C	
Storage Temperature	-30C to 50C	
Storage Bag Dimensions	340x340x100mm	380x380x100mm
Weight	320g	350g
Insertion / Pull Out Force	>100N	
Mechanical Operations	10,000	
IP Rating	IP54	
Certifications	IEC 62196.1 2014, IEC 62196.2 2016	

ICSL5



ICSL10



Connect with iCS

The only link you'll need
for tech support, socials and lots more!
@icsintelligentchargingsystems

Email: info@intelligentchargingsystems.co.uk

www.intelligentchargingsystems.co.uk

iCS_ICSL5&ICSL10_Data_Sheet_Rev01